

496

2,0 mm URT

Technisches Datenblatt

496x496 FRAME
TOP-LEVEL LED
BLACK-FACE LED
KONKAV | KONVEX | BODEN
ALUMINIUM-STANDSYSTEM
URT-VERSIEGELUNG



| | |
|---------------------------|---|
| Pixelpitch | 2,06 |
| Helligkeit | > 1.000 nit |
| SMD-Typ | LEDitgo BF1010 URT |
| SMD Merkmale | Top-Level, Black-Face |
| Farbtiefe | 14 Bit (18 Bit+ Modus, 22 Bit Image Booster) |
| Auflösung | 240 x 240 Pixel |
| Receivingcard | A8s |
| Refreshrate | > 3.840 Hz |
| Horiz. Blickwinkel | +170° / -170° |
| Vert. Blickwinkel | +170° / -170° |
| Kontrast | > 3.000:1 |
| Nennleistung | Typ. 80 W / Max. 110 W |
| Abmessungen | 496 x 496 x 55 mm (BxHxT) |
| Gewicht | 7,5 kg |
| IP Klasse | IP 40 |
| Temperaturbereich | -20° C bis +50°C |
| Produktighlights | 90° biegsame IMs, Konkav-LED Konvex-LED, Boden-LED, Quader-Tiles, und zahlreiches Zubehör zur Integration in Aluminium-Standsysteme Signifikant weniger mechanische Schäden durch speziell vergossene Module |

Zertifizierungen

