




aD-10

Technisches Datenblatt

960 x 960 mm

NOVASTAR A5S PLUS RECEIVINGCARD
HIGH BRIGHTNESS
HIGH-CONTRAST
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
100% FRONT- & BACKSERVICE



| | |
|----------------------------|---|
| Pixelpitch | 10,00 mm |
| Helligkeit | 7.000 nit |
| Gewicht | 26,5 kg |
| Nennleistung | Typisch 86 W max. 257 W |
| SMD-Typ | SMD2727 |
| SMD Merkmale | High-Brightness, High-Contrast, High-Level |
| Farbtiefe | Bis zu 14 Bit |
| Auflösung | 96 x 96 px |
| LED Treiberchip | ICN2038S |
| Receivingcard | Novastar A5s+ |
| Scantyp | 1/2 |
| Refreshrate | ≥ 1.920 Hz |
| Horiz. Blickwinkel | +140° / -140° |
| Vert. Blickwinkel | +140° / -140° |
| Kontrast | > 4.000:1 |
| Spannungsbereich | AC 110-220V / 50 Hz |
| Stromanschluss | Seetronic TR1 |
| Abmessungen (BxHxT) | 960 x 960 mm T= 108 mm |
| IP Klasse | IP65 IP54 |
| Temperaturbereich | -20°C bis +50°C (Im Betrieb) -20°C bis +50°C (Lagernd) |
| Produkthighlights | Quick-Lock-System, Magnetic Fast-Rigg, 100% Front- & Backservice |
| Zertifizierungen |    EMC |