





HIGH-BRIGHTNESS
HIGH-CONTRAST
BLACK-FACE
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
CLIMBABLE FRAME
FAST REPLACEABLE BACKBOX

Pixelpitch	2,9 mm
Helligkeit	1.600 Nits kalibriert (1.800 max.)
SMD-Typ	Nationstar 2121 3-in-1 RGB
SMD Merkmale	Full-Black, High-Brightness, High-Contrast, High-Level
Farbtiefe	16 Bit pro Farbkanal
Auflösung	168 x 168 Pixel
LED Treiberchip	MBI5252
Receivingcard	MRV270
Scantyp	1/14
Refreshrate	≥ 3840 Hz
Horiz. Blickwinkel	+85°/-85°
Vert. Blickwinkel	+85°/-85°
Kontrast	> 5.000:1
Nennleistung in W	Typisch 60W / max. 160W
Spannungsbereich	AC 88-264V/ 50-60 Hz
Stromanschluss	NeutrikpowerCON
Abmessungen	500 x 500 x 100 mm (BxHxT)
Gewicht	9,5 kg
IP Klasse	IP40
Temperaturbereich	Im Betrieb: -30°C bis + 45°C Lagernd: -10°C bis + 55°C
Produkthighlights	Quick-Lock-System, Magnetic Fast-Rigg, Climbable Frame, Fast Replaceable Backbox
Zertifizierungen	   EMC

